

PT-D800W Label Printer

LABELS THAT STICK. P-touch

P. touch D800W

brother.com.au

Take your labelling to a whole new level of professionalism

Design and print durable labels with ease thanks to a large keyboard and USB/WiFi connectivity that lets you print directly from your laptop or smartphone.



Key Features:



High quality label printing

Today, flexibility is key. The PT-D800W has a wide range of tape colour combinations and widths as well as high-speed/high resolution print capabilities. So, whether you choose from the many built-in options, or to use the USB/WiFi connectivity to print directly from your PC, Mac, Smartphone or tablet, the PT-D800W is simply perfect for all your labelling tasks such as cable marking, document archiving and asset labelling.



Advanced print engine for fast, efficient labelling

The PT-D800W prints labels from 3.5mm up to 36mm wide, and, with a 32mm print height offers near edge-to-edge printing. Additionally, a print speed of up to 60mm/second dramatically reduces the printing time – particularly useful when using the advanced cutter to produce a long strip of easy to peel labels.



Powerful design software for PC and Mac

P-touch Editor boasts advanced features normally found in expensive desktop applications such as industry standard 1D and 2D barcodes, and import of logos and other graphics. It also allows you to use the fonts installed on your computer, as well as link to a Microsoft Excel® spreadsheet or a .csv file to print multiple labels quickly and efficiently.



Wireless connectivity for ultimate flexibility

The Brother iPrint&Label app connects wirelessly using Wi-Fi direct to let you design simple labels on your iOS or Android device. Or, simply connect it to your office wireless network and allow your team to print labels from their PC or Mac whenever required. If you need to identify electrical and data cabling and equipment, use the specialised Brother Cable Label Tool app to quickly print labels for wrapping around cables or for sticking to faceplates, electrical distribution boards, cabinets, servers and other equipment.



Store your own label templates and logos

Create a label design template on your PC, then transfer to the built-in memory of the PT-D800W. This powerful feature lets you edit the text before printing, ensuring your labels all use the same uniform format. You can also upload your own images such as company logos or specialist symbols for printing when you're away from your PC.



The ultimate in portable label printing

Featuring a full-size laptop style keyboard with integrated easy-to-read graphic display, the PT-D800W can be used on-site to instantly create durable labels on demand. Use the many built-in templates, block layouts and hundreds of office and industrial symbols to quickly create labels for any application. Also, the built-in carry handle, storage area for tape cassettes and AC adapter mean you can easily take the PT-D800W on-site, wherever required.

	Technical Specifications for the PT-D800W
	General
Hardware Type	Desktop
Keyboard	Qwerty & Numeric
Display Type	LCD (backlit)
LCD Display	17 Characters x 4 line LCD
Built In Languages	20 languages: English, German, French, Spanish, Portuguese, Portuguese-Bra, Italian, Dutch, Danish, Norwegian, Swedish, Finish, Hungarian, Czech, Polish, Romanian, Slovene, Slovak, Croatian, Turkish
Buttons & LED	Label Status, Battery, Power, Feed&cut, Wi-Fi
Feed	Yes
Cable Labelling Function	4 kinds: Cable Wrap, Cable Flag, FacePlate, Patch Panel
Label Collection	Available via iPrint&Label (Mobile App)
	Labeller
Print Engine	Direct thermal
Print Speed	60 mm/sec
Printer Resolution	360 dpi
Emulation	Raster mode
Max Print Height	32mm
Tape Cutter	Auto
Tape Length Setting	Auto
Tape Length	8M
Tape colour detection	Yes
Tape Included	TZe-261 (36mm Black/White 8m)
Fonts Labeller	14 fonts: Helsinki, Brussels, Belgium, Florida, Los Angels, San Diego, US,Calgary, Atlanta, Adams, Brunei Sofia, Germany, LetterGothic or PC Select
Font Sizes	7 kinds: Auto/ 6/ 9/ 12/ 18/ 24/ 36/ 42pt or PC Select
Font Styles	12 styles: Normal, Bold, Outline, Shadow, Solid, Italic (Bold, Outline, Shadow, Solid), Vertical, vertical bold or PC select
Font Widths	5 kinds: ×1 / ×3/2 / ×2 / ×½ / ×2/3
Frames and Backgrounds	99 Frames
Characters and Symbols	673 Characters / 465 Symbols
Time & Date feature	Yes
Memory	Text Buffer: 280 Characters / Label Buffer: 1,500 Characters
Barcodes	9 protocols: CODE39, ITF 2/5, EAN13, EAN8, UPC-A, UPC-E, CODABAR, GS1-128(UCC/EAN128), CODE128
Auto Number / Format	Yes
Underline	Yes
Multi Line Print	17
Repeat Print	Yes (1-99)
Mirror Print	Yes
Vertical Print	Yes (in the style setting)
Print Preview	Yes (Label / Print Preview)
	Software
Software Supplied	Windows: P-Touch Editor 5.4, Printer Driver / Mac: P-Touch Editor 5.3, Printer Driver
Interface	Windows USB 2.0 / Mac USB 2.0 and Wireless IEEE
Operating System	802.11b/g/n Windows Vista(R), 7/8/8.1/10, / Mac OS X 10.8 or greater
	802.11b/g/n Windows Vista(R), 7/8/8.1/10, / Mac OS X 10.8 or greater
Operating System	802.11b/g/n Windows Vista(R), 7/8/8.1/10, / Mac OS X 10.8 or greater Consumables
Operating System Tape Type	802.11b/g/n Windows Vista(R), 7/8/8.1/10, / Mac OS X 10.8 or greater Consumables TZe laminated & non-laminated and HSe (Heat-shrink Tube)
Operating System Tape Type	802.11b/g/n Windows Vista(R), 7/8/8.1/10, / Mac OS X 10.8 or greater Consumables TZe laminated & non-laminated and HSe (Heat-shrink Tube) 3.5mm, 6mm, 9mm, 12mm, 18mm, 24mm, and 36mm
Operating System Tape Type Tape Widths	802.11b/g/n Windows Vista(R), 7/8/8.1/10, / Mac OS X 10.8 or greater Consumables TZe laminated & non-laminated and HSe (Heat-shrink Tube) 3.5mm, 6mm, 9mm, 12mm, 18mm, 24mm, and 36mm Weight and Measurements
Operating System Tape Type Tape Widths Dimensions	802.11b/g/n Windows Vista(R), 7/8/8.1/10, / Mac OS X 10.8 or greater Consumables TZe laminated & non-laminated and HSe (Heat-shrink Tube) 3.5mm, 6mm, 9mm, 12mm, 18mm, 24mm, and 36mm Weight and Measurements 338 x 188 x 151mm ; 338 x 188 x 173mm (with keyboard)
Operating System Tape Type Tape Widths Dimensions	802.11b/g/n Windows Vista(R), 7/8/8.1/10, / Mac OS X 10.8 or greater Consumables TZe laminated & non-laminated and HSe (Heat-shrink Tube) 3.5mm, 6mm, 9mm, 12mm, 18mm, 24mm, and 36mm Weight and Measurements 338 x 188 x 151mm ; 338 x 188 x 173mm (with keyboard) 3.3kg (With Keyboard)
Operating System Tape Type Tape Widths Dimensions Weight	802.11b/g/n Windows Vista(R), 7/8/8.1/10, / Mac OS X 10.8 or greater Consumables TZe laminated & non-laminated and HSe (Heat-shrink Tube) 3.5mm, 6mm, 9mm, 12mm, 18mm, 24mm, and 36mm Weight and Measurements 338 x 188 x 151mm ; 338 x 188 x 173mm (with keyboard) 3.3kg (With Keyboard) Power Supply
Operating System Cape Type Tape Widths Dimensions Weight Batteries (Not included)	802.11b/g/n Windows Vista(R), 7/8/8.1/10, / Mac OS X 10.8 or greater Consumables TZe laminated & non-laminated and HSe (Heat-shrink Tube) 3.5mm, 6mm, 9mm, 12mm, 18mm, 24mm, and 36mm Weight and Measurements 338 x 188 x 151mm ; 338 x 188 x 173mm (with keyboard) 3.3kg (With Keyboard) Power Supply AD9100ESA (included)
Operating System Comparison Comparison	802.11b/g/n Windows Vista(R), 7/8/8.1/10, / Mac OS X 10.8 or greater Consumables TZe laminated & non-laminated and HSe (Heat-shrink Tube) 3.5mm, 6mm, 9mm, 12mm, 18mm, 24mm, and 36mm Weight and Measurements 338 x 188 x 151mm ; 338 x 188 x 173mm (with keyboard) 3.3kg (With Keyboard) Bower Supply AD9100ESA (included) Li-ion Battery Pack (PA-BT-4000LI), Battery Base (PA-BB-003)
Operating System Comparison Comparison	802.11b/g/n Windows Vista(R), 7/8/8.1/10, / Mac OS X 10.8 or greater Consumables TZe laminated & non-laminated and HSe (Heat-shrink Tube) 3.5mm, 6mm, 9mm, 12mm, 18mm, 24mm, and 36mm Weight and Measurements 338 x 188 x 151mm ; 338 x 188 x 173mm (with keyboard) 3.3kg (With Keyboard) Power Supply AD9100ESA (included) Li-ion Battery Pack (PA-BT-4000Ll), Battery Base (PA-BB-003) 20 minutes - Battery, 30 minutes - Li-ion battery
Operating System Comparison Comparison	802.11b/g/n Windows Vista(R), 7/8/8.1/10, / Mac OS X 10.8 or greater Consumables TZe laminated & non-laminated and HSe (Heat-shrink Tube) 3.5mm, 6mm, 9mm, 12mm, 18mm, 24mm, and 36mm Weight and Measurements 338 x 188 x 151mm ; 338 x 188 x 173mm (with keyboard) 3.3kg (With Keyboard) Power Supply AD9100ESA (included) Li-ion Battery Pack (PA-BT-4000LI), Battery Base (PA-BB-003) 20 minutes - Battery, 30 minutes - Li-ion battery 1 hour - AC Adaptor
Operating System Cape Type Tape Widths Dimensions Weight Batteries (Not included) Optional Power (Not included) AC Adaptor Auto Power Off	802.11b/g/n Windows Vista(R), 7/8/8.1/10, / Mac OS X 10.8 or greater Consumables TZe laminated & non-laminated and HSe (Heat-shrink Tube) 3.5mm, 6mm, 9mm, 12mm, 18mm, 24mm, and 36mm Weight and Measurements 338 x 188 x 151mm ; 338 x 188 x 173mm (with keyboard) 3.3kg (With Keyboard) Power Supply AD9100ESA (included) Li-ion Battery Pack (PA-BT-4000LI), Battery Base (PA-BB-003) 20 minutes - Battery, 30 minutes - Li-ion battery 1 hour - AC Adaptor Other

Optional Accessories

PA-BB-003

Battery base for Lithium-ion battery



PA-BT-4000LI

Lithium-ion rechargeable battery

















Water Resistant

Temperature Resistant

Abrasion Resistant

Fade Resistant

Chemical Laminated Resistant


ed Easy Peel

Strong Adhesion



Working with you for a better environment

At Brother, our green initiative is simple. We strive to take responsibility, act respectfully and try to make a positive difference to help build a society where sustainable development can be achieved. We call this approach Brother Earth.



PT-D800W | Page 4

Brother

Earth



